



PURONOL - SE

SULPHO ESTER BASED FATLIQUOR FOR ALL TYPES OF SOFT LEATHER
(AOX FREE)

| | |
|--------------------|--|
| Product name | : PURONOL SE |
| Appearance | Light brown to reddish brown transparent liquid |
| Character | : Anionic sulphonated synthetic ester blended with paraffins |
| PH of 10% solution | : 7.0 to 8.0 Active matter (%w/w) - 60% ± 2 |
| Light fastness | : very good |
| Method of dilution | : Can be diluted with cold or warm water in the ratio of 1:4 it will give a milky emulsion. |
| Properties | : Penetrated deep into the leather even without additional use of other oils. Thus gives a well balanced fat liquoring effect throughout the thickness of the leather. Suitable for all types of soft leather. |
| Compatibility | : Compatible with non-ionic and anionic products. |
| Safety | : A non hazard product and can be handled With normal care. Any contact with eye and / Or spillage on skin should be washed thoroughly in running water. |
| Storage | : 6 Months shelf life when stored indoors in sealed containers. Protect from moisture and exposure to sunlight. |

Note : If affected by frost the product should be heated to the temperature of 20 to 25° C and stirred before using.

APPLICATION:

% based on shaved weight

Fuel chrome cow Soft Upper :

| | |
|----|---------------|
| 3% | Puronol - SE |
| 2% | Puronol - VG |
| 2% | Puronol - GWF |

Fuel chrome Goat suede :

| | |
|----|---------------|
| 3% | Puronol - LN |
| 2% | Puronol- SE |
| 3% | Puronol - BSF |

Fuel chrome sheep nappa :

| | |
|----|-----------------|
| 5% | Puronol - SE |
| 2% | Puronol - LN |
| 2% | Puronol - SS 20 |
| 2% | Puronol - SF |

