



TECHNICAL DATA SHEET

PUROTAN –FBS **Sulfone Syntan for White Leathers**

Product name	: PUROTAN FBS
Appearance	: Dark brown Liquid
Moisture Content	: 50 ± 2%
pH of 10% aqueous solution	: 6.50-7.00
Light fastness	: Excellent

PROPERTIES :

PUROTAN FBS increase the shrinkage temperature considerable hence it is more suitable tanning and retanning agent after wet white pretanning. **PUROTAN FBS** has very good tanning properties therefore suitable for metal-free tanning system. **PUROTAN FBS** imparts uniform filling with soft and round handle leathers treated with **PUROTAN FBS** gives uniform milling. **PUROTAN FBS** has mild astringency hence leathers will have fine grain **PUROTAN FBS** can also be used along with other tanning agents.

Our range of liquid syntans has very low electrolyte content, thus low effluent pollution. Also have very less BOD and COD in the effluent. Has an advantage of easy feeding in to drums where the automation methods are adopted.

SAFETY :

A non hazard product can be handled with normal care. Any contact with eyes and/or spillage on skin should be washed thoroughly in running water.

STORAGE :

6 months shelf life when stored in doors in sealed containers. Protect from moisture and exposure to sunlight.

APPLICATION :

In general 4.0-8.0 % can be applied in retanning based on shaved weight for wet white 20-25 % based on shaved weight in 2 or 3 stages.