



TECHNICAL DATA SHEET

PURONOL -HD

(SULFO SUCCINIC ESTER BASE FAT LIQUOR)

Product name	: PURONOL-HD
Appearance	: Off - White Paste.
Character	: Anionic synthetic fatliquor based on Sulpho succinic esters.
pH of 10% solution	: 7.0 to 8.5
Active matter (% w/w)	: 55% ± 2
Solubility	: Soluble in Water
Light fastness	: Excellent
Method of dilution	: Can be used as single fat liquor (15%) or diluted with warm water in the ratio of 1:3 at 60°C while stirring.

PROPERTIES : **PURONOL HD** is synthetic fatliquor based on sulphited esters. **PURONOL HD** can be used as a sole fatliquor in processing of upholstery, gloving and garment leather. **PURONOL HD** provides extra body and softness and also gives excellent life fastness to the leathers. **PURONOL HD** is a light fast product and can be used for white and other pastel coloured leathers. **PURONOL HD** produces highly soft and supple leather without lossness.

EMULSION

INSTRUCTIONS : To the required quantity of **PURONOL HD** add slowly three times of its own weight of water at 60°C, while stirring.

SAFETY : A non hazard product and can be handled. with normal care. Any contact with eye and / or spillage on skin should be Washed thoroughly in running water.

STORAGE : 6 months shelf life when stored indoors in sealed containers. Protects from moisture and exposure to sunlight.

NOTE : If affected by frost the product should be heated to the temperature of 20 to 25° C and stirred before using.



TECHNICAL DATA SHEET

PURONOL-HD

APPLICATION

Upholstery and Gloving Leather

Fatliquoring

15% PURONOL HD
(As single fatliquor)

Garment Leather

Fat liquoring

10% PURONOL HD

Milled Leather

Fat Liquoring

15% PURONOL HD