



TECHNICAL DATA SHEET

PUREWAX –RCWH

(BURNISHING WAX)

PUREWAX-RCWH is a blend of Syntheticoils and special waxes which provides dark pull-up and waxy feel to the coated leathers.

CHARACTERISTICS:

Appearance	: creamish white
Nature	: Synthetic and Natural oilsSolvent dilutable
Solid content	: 100%

PUREWAX-RCWH is solvent dilatable blend of special oils and waxes which designed for providing dark pull-up effect of leather.

PUREWAX-RCWH is normally applied on leather with the help of heated roller coated leathers are dried and aired off over night and then plated at 100C-120C/50bar or Fin flexed at 130C to get the desired effect.

A second coat and subsequent plating may also be required for heavy stuffed leathers or for leathers with high/uneven absorption.

PUREWAX-RCWH confers warm and waxy touch to the leather. Leather defects are effectively masked due to the darkening provided by it after plating. Leather coated with PUREWAX-RCWHdo not develops bad smell even on prolonged aging.

The leather coated with PUREWAX-RCWH may be finished lightly with carefully prepared season of protein or resin binders followed by fixing with formalin or lacquer emulsion. Passing through contilux will result in the leather having pleasant handle and gloss.



TECHNICAL DATA SHEET

PUREWAX –RCWH

(BURNISHING WAX)

SUGGESTED APPLICATION :

Apply as such on stuffed leathers with the help of heated roller coating machine. Air off over night, kiss plate at high temperature, apply one more coat if required, contilux at 125°C/50bar.

SHELF LIFE:

12 months when stored free from moisture in a dry, cool place in closed containers at ambient temperature.

As practices vary from tannery to tannery, we recommend that our suggestions be tested before commercial use. All information is without liability.