



TECHNICAL DATA SHEET

PUREWAX –PWX

(HOT MELT WAX)

PUREWAX-PWX is a blend of synthetic oil and special wax which provides pullup effect and warm waxy feel to the cooled leather .

Appearance	: Milky White wax with a blend of synthetic oil and special wax
Solid content	: 100%
Solubility	: Soluble in organic solvent

PUREWAX PWX is a special wax synthetic oil blend designed for providing pullup effect on leather. **PUREWAX PWX** is normally applied on leather with the help of heated roller coater. Coated leathers are dried and aired off overnight and then plated at 100°C -120°C /50 bar (or) finiflamed at 130°C to get defined effect. A second coat and subsequent plating may also be required for heavy scuffed leathers (or) for leather with high / uneven absorption.

PUREWAX PWX confers warm and waxy touch to the leather. Leather defects are effectively masked due to the dirking provide by it after plating. Leather coated with **PUREWAX PWX** do not develop bad smell even on prolonged aging. The leather coated with **PUREWAX PWX** may be finished lighting with carefully prepared season of protein (or) resin binders followed by fixing with formalin (or) lacquer emulsion passing through contilux will result in the leather having pleasant handle and gloss.

SUGGESTED APPLICATION

Apply as such on snuffed with the help of heated roller coating machine. Airs off over height, plate at high temperature apply one more coat if required contilux at 125°C / 50 bar.



TECHNICAL DATA SHEET

PUREWAX –PWX

(HOT MELT WAX)

SHELF LIFE:

12 months when stored free from moisture in a dry, cool place in closed containers at ambient temperature.

As practices vary from tannery to tannery, we recommend that our suggestions be tested before commercial use. All information is without liability.